

# SAFETY DATA SHEET

Issuing Date 5/01/2015



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

**Product Name** Safer® Brand Mosquito & Tick Killer

### Other means of identification

**UN-No.** UN1170

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Insecticide - Crawling Bug - Non-Aerosol

**Uses advised against** It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

### Details of the supplier of the safety data sheet

**Supplier Name** Woodstream Corp.  
**Supplier Address** 69 North Locust St.  
Lititz  
PA  
17543  
US  
**Supplier Phone Number** Phone:(717) 626-2125  
Fax:(717) 626-1912  
Contact Phone(800) 800-1819  
**Supplier Email** mandre@woodstream.com  
**Emergency telephone number**

## 2. HAZARDS IDENTIFICATION

### Classification


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Flammable liquids	Category 2

### GHS Label elements, including precautionary statements



**Emergency Overview**

<b>Signal word</b>	<b>Danger</b>		
<b>Hazard Statements</b>	Causes serious eye irritation Highly flammable liquid and vapor		
			
<b>Appearance</b>	Translucent	<b>Physical State</b>	Liquid
			<b>Odor</b> Alcohol

**Precautionary Statements - Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/protective clothing/eye protection/face protection

**Precautionary Statements - Response**

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention

**Skin**

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

**Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity**

40.39% of the mixture consists of ingredient(s) of unknown toxicity

**Other information**

Toxic to aquatic life with long lasting effects  
 PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

**Interactions with Other Chemicals**

Use of alcoholic beverages may enhance toxic effects.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%	Trade Secret
Ethyl alcohol	64-17-5	30 - 60	*
Isopropyl alcohol	67-63-0	7 - 13	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

**4. FIRST AID MEASURES**

**First aid measures**

**General Advice**

Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.

**Eye Contact**

In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.

**Skin Contact**

Wash skin with soap and water.

**Inhalation**

Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult.

**Ingestion**

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.

**Self-protection of the first aider**

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**Most important symptoms and effects, both acute and delayed**

**Most Important Symptoms and Effects** Burning sensation.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician**

Keep victim warm and quiet.



## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam. Water spray, fog or alcohol-resistant foam. Use water spray or fog; do not use straight streams.

### Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

### Specific Hazards Arising from the Chemical

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

#### **Uniform Fire Code**

Flammable Liquid: I-B  
Irritant: Liquid  
Highly Toxic: Liquid  
Toxic: Liquid

### Hazardous Combustion Products

Carbon oxides.

### Explosion Data

**Sensitivity to Mechanical Impact** No.

**Sensitivity to Static Discharge** Yes.

### Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

#### **Other Information**

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

### Environmental Precautions

#### **Environmental Precautions**

Prevent entry into waterways, sewers, basements or confined areas.

### Methods and material for containment and cleaning up

#### **Methods for Containment**

A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

#### **Methods for cleaning up**

Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.



**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Handling**

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

**Conditions for safe storage, including any incompatibilities**

**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

**Incompatible Products**

Strong oxidizing agents. Acids. Chlorinated compounds.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm 10% LEL TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m <sup>3</sup> TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>

*ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health*

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

**Appropriate engineering controls**

**Engineering Measures**

- Showers
- Eyewash stations
- Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**

None required for consumer use. If splashes are likely to occur: Tight sealing safety goggles.



<b>Skin and Body Protection</b>	Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves. Antistatic boots.
<b>Respiratory Protection</b>	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
<b>Hygiene Measures</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Odor</b>	Alcohol
<b>Appearance</b>	Translucent	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks/ Method</u>
pH	8	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	22 C / 72 F	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Completely soluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	12.5	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	

**Other Information**

<b>Softening Point</b>	No data available
<b>VOC Content (%)</b>	No data available
<b>Particle Size</b>	No data available
<b>Particle Size Distribution</b>	



## 10. STABILITY AND REACTIVITY

### **Reactivity**

No data available.

### **Chemical stability**

Stable under recommended storage conditions.

### **Possibility of Hazardous Reactions**

None under normal processing.

### **Hazardous Polymerization**

Hazardous polymerization does not occur.

### **Conditions to avoid**

Heat, flames and sparks.

### **Incompatible materials**

Strong oxidizing agents. Acids. Chlorinated compounds.

### **Hazardous Decomposition Products**

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### **Information on likely routes of exposure**

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information.
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
<b>Eye Contact</b>	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. May cause redness, itching, and pain. May cause temporary eye irritation.
<b>Skin Contact</b>	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl alcohol 64-17-5	-	-	= 124.7 mg/L ( Rat ) 4 h
Isopropyl alcohol 67-63-0	= 4396 mg/kg ( Rat )	= 12800 mg/kg ( Rabbit )	= 16000 ppm ( Rat ) 8 h

### **Information on toxicological effects**

**Symptoms** May cause redness and tearing of the eyes.



**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Mutagenic Effects** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

<b>Chemical Name</b>	<b>ACGIH</b>	<b>IARC</b>	<b>NTP</b>	<b>OSHA</b>
Ethyl alcohol 64-17-5	A3	Group 1	Known	X
Isopropyl alcohol 67-63-0		Group 3		X

*ACGIH (American Conference of Governmental Industrial Hygienists)  
 A3 - Animal Carcinogen  
 IARC (International Agency for Research on Cancer)  
 Group 1 - Carcinogenic to Humans  
 Group 3 - Not Classifiable as to Carcinogenicity in Humans  
 NTP (National Toxicology Program)  
 Known - Known Carcinogen  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 X - Present*

**Reproductive Toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic Toxicity** No known effect based on information supplied. Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.

**Target Organ Effects** Eyes. Blood. Central Nervous System (CNS). Liver. Reproductive System. Respiratory system. Skin. Kidney. Spleen. Systemic Toxicity.

**Aspiration Hazard** No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

- ATEmix (oral)**  
12,751.00 mg/kg
- ATEmix (dermal)**  
31,840.00 mg/kg (ATE)
- ATEmix (inhalation-dust/mist)**  
50.40 mg/l
- ATEmix (inhalation-vapor)**  
206.00 ATEmix





## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Ethyl alcohol 64-17-5		96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 13400 - 15100 mg/L (Pimephales promelas) 96h LC50: 12.0 - 16.0 mL/L (Oncorhynchus mykiss)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	48h LC50: 9268 - 14221 mg/L 48h EC50: = 2 mg/L 24h EC50: = 10800 mg/L
Isopropyl alcohol 67-63-0	96h EC50: > 1000 mg/L (Desmodesmus subspicatus) 72h EC50: > 1000 mg/L (Desmodesmus subspicatus)	96h LC50: > 1400000 µg/L (Lepomis macrochirus) 96h LC50: = 11130 mg/L (Pimephales promelas) 96h LC50: = 9640 mg/L (Pimephales promelas)		48h EC50: = 13299 mg/L

### Persistence and Degradability

No information available.

### Bioaccumulation

Chemical Name	Log Pow
Ethyl alcohol 64-17-5	-0.32
Isopropyl alcohol 67-63-0	0.05

### Other adverse effects

No information available.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

<b>Disposal methods</b>	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
<b>Contaminated Packaging</b>	Dispose of contents/containers in accordance with local regulations.
<b>US EPA Waste Number</b>	D001

### **California Hazardous Waste Codes 232**

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Ethyl alcohol 64-17-5	Toxic Ignitable
Isopropyl alcohol 67-63-0	Toxic Ignitable

## 14. TRANSPORT INFORMATION



**DOT**

UN-No.	UN1170
Proper Shipping Name	ETHANOL
Hazard Class	ORM-D
Description	CONSUMER COMMODITY, ORM-D, NONE
Emergency Response Guide Number	127

**TDG**

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	II
Description	UN1170, ETHANOL SOLUTION, 3, II

**MEX**

UN-No.	UN1170
Proper Shipping Name	ETHANOL IN SOLUTION
Hazard Class	3
Packing Group	II
Description	UN1170, ETHANOL IN SOLUTION, 3, II

**ICAO**

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	II
Description	UN1170, ETHANOL SOLUTION, 3, II

**IATA**

UN-No.	UN1170
Proper Shipping Name	Ethanol Solution
Hazard Class	3
Packing Group	II
Description	UN1170, ETHANOL SOLUTION, 3, II

**IMDG/IMO**

UN-No.	UN1170
Proper Shipping Name	<b>Ethanol Solution</b>
Hazard Class	3
Packing Group	II
EmS No.	F-E, S-D
Description	UN1170, ETHANOL SOLUTION, 3, II, (22°C C.C.)

**RID**

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	II
Classification code	F1
Description	UN1170, ETHANOL SOLUTION, 3, II

**ADR**

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	II
Classification code	F1



**Tunnel restriction code** (D/E)  
**Description** UN1170, ETHANOL SOLUTION, 3, II

**ADN**

**UN-No.** UN1170  
**Proper Shipping Name** ETHANOL SOLUTION  
**Hazard Class** 3  
**Packing Group** II  
**Classification code** F1  
**Special Provisions** 144, 601  
**Description** UN1170, ETHANOL SOLUTION, 3, II  
**Limited Quantity** 1 L  
**Ventilation** VE01

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies  
**DSL** All components are listed either on the DSL or NDSL.  
**IECSC** -

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Isopropyl alcohol - 67-63-0	67-63-0	7 - 13	1.0

**SARA 311/312 Hazard Categories**

**Acute Health Hazard** Yes  
**Chronic Health Hazard** No  
**Fire Hazard** Yes  
**Sudden release of pressure hazard** No  
**Reactive Hazard** No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethyl alcohol - 64-17-5	Carcinogen Developmental



Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Ethyl alcohol 64-17-5		X			
Isopropyl alcohol 67-63-0	X	X	X	X	
Pyrethrum 8003-34-7	X	X	X	X	
Acetic acid 64-19-7	X	X	X	X	

**International Regulations**

**Mexico**

**National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Ethyl alcohol 64-17-5 ( 30 - 60 )		Mexico: TWA 1000 ppm Mexico: TWA 1900 mg/m <sup>3</sup>
Isopropyl alcohol 67-63-0 ( 7 - 13 )		Mexico: TWA 400 ppm Mexico: TWA 980 mg/m <sup>3</sup> Mexico: STEL 500 ppm Mexico: STEL 1225 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

**Canada**

**WHMIS Hazard Class**

B2 - Flammable liquid

D2A - Very toxic materials



**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards 2</b>	<b>Flammability 3</b>	<b>Instability 0</b>	<b>Physical and Chemical Hazards - Personal Protection</b> X
<b>HMIS</b>	<b>Health Hazards 2</b>	<b>Flammability 3</b>	<b>Physical Hazard 0</b>	

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Revision Date** 19-Sep-2014  
**Revision Note** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

