

<b>Product Name:</b>	<b>Bluelab Multimedia pH Meter</b>
<b>Product Code:</b>	<b>METMULTI</b>
<b>UPC Code:</b>	9421024920951
<b>Country of Origin:</b>	New Zealand
<b>Tariff Code:</b>	9027.80.80.30
<b>Shipping Quantity:</b>	Sold as singular unit
<b>Packaging Information:</b>	
<b>Packaged Weight:</b>	0.39 kg / 0.86 lb
<b>Packaged Length:</b>	180 mm / 7.086 in
<b>Packaged Width:</b>	110 mm / 4.33 in
<b>Packaged Height:</b>	83 mm / 3.267 in

**Sales Description:**

*NOTE: this copy can be used in brochures, catalogues or online*

**The perfect, portable way to accurately measure and monitor pH levels in a wide range of media.**

Combine the Bluelab® Multimedia pH Meter and Bluelab® Leap™ pH Probe to take fast accurate measurements in nutrient solution, soil, coco coir, rockwool, potting mix and many other media types.

Calibration is simple with one push button on the meter and fresh Bluelab® Calibration Solutions. Successful calibration indicator is displayed on screen for 30 days to indicate when re-calibration is required.

Team with the Bluelab® Solutions and the convenient Bluelab® Carry Case. Replacement Bluelab® pH or Leap™ pH Probe available too.

2 metre / 6.6 foot standard cable

**Features:**

- Test more with a faster sensor response and direct measurements from substrates
- Multimedia friendly, for measurements across a range of environments
- Toughened spear tip for direct root-zone measurements
- Simple two point calibration process with 30 day calibration indicator
- Backlit LCD display, low battery indicator, auto off function

**Product Guarantee:**

Five year free repair or replacement guarantee\*.  
\* Six months for Leap pH Probe.



**Product Image:**



**Product images available for Screen or Web use:**

- Bluelab-MultimediapHMeter-MR-flat-RGB.jpg
- Bluelab-MultimediapHMeter-WEB.jpg
- Bluelab-MultimediapHMeter-WEB-Sml.jpg

**Product images available for PRINT:**

*Note: these images are high resolution in CMYK.*

- Bluelab-MultimediapHMeter-MR-flat-CMYK.tif

**Technical Specifications:**

<b>Measurement Range:</b>	0.0 – 14.0 pH
<b>Resolution:</b>	0.1 pH
<b>Accuracy at 25°C / 77°F:</b>	± 0.1 pH
<b>Operating Environment:</b>	0 – 50°C / 32 – 122°F
<b>Calibration:</b>	Two point, pH 7.0 & pH 4.0 or pH 10.0
<b>Power Source:</b>	2 x AAA alkaline batteries

{This Product Information Sheet is NOT intended for distribution to end users.}