

POLYETHYLENE TUBING

FINEST LOW DENSITY POLYETHYLENE RESIN AVAILABLE



APPLICATIONS

- Greenhouse, nursery, indoor or outdoor
- Subsurface, surface and suspension from vine
- For use with riser lines

Greenhouse & Nursery Applications



PE Tubing with On-Line Drillers in Nursery



PE Tubing with Multi-Outlet Drillers for Containers

PRODUCT ADVANTAGES

- Made from the highest quality low density resins.
- Excellent Ultra-Violet (UV) and acid resistance.
- Available in black or bright white color, standard coil lengths or large diameter reels to meet your specific needs.
- Bright white tubing is opaque to prevent algae growth, withstand heat and harsh chemicals while producing cooler water temperatures.
- Every reel undergoes a battery of tests to ensure high quality manufacturing standards are met.

POLYETHYLENE TUBING ACCESSORIES



ON-LINE DRIPPERS Pressure Compensating or Non-Compensating

Designed with a large flow path allowing particles to pass freely through for long-term efficient operation. Can be installed anywhere along the tubing. Available in pressure compensating or non-compensating options with multiple flow rates.

ORDERING AND TECHNICAL INFORMATION – BRIGHT WHITE POLYETHYLENE TUBING

Nominal Diameter		Nominal Wall Thickness	Nominal Diameter	Coil Length	Maximum Working Pressure (psi)	Netafim Model Number	Hawthorne Part Number
Inside	Outside						
0.560"	0.660"	0.050"	17 mm	500'	62	14BW056066-05	HGC747559
0.820"	0.940"	0.060"	3/4 in.	100'	51	14BW082094-01	HGC747564
0.820"	0.940"	0.060"	3/4 in.	500'	51	14BW082094-05	HGC747750
1.060"	1.200"	0.070"	1 in.	100'	44	14BW106120-01	HGC747566

NETAFIM OFFERS THE INDUSTRY'S LONGEST WARRANTY

Blank Polyethylene Tubing is warranted to be free from original defects in materials and workmanship for a period of seven (7) years and ten (10) years for environmental stress cracking (surface or subsurface applications). This warranty applies only to products with a wall thickness of 35 mil or greater.