



DOSATRON®


WATER POWERED DOSING TECHNOLOGY

14 GPM: D14MZ2VFBPHY

Product Specifications

Call 800-523-8499 to order the Dosatron for your specific application

Dilution Range:	1:500 to 1:50 (0.2% to 2%)
Ratio Range mL:	7.5 to 75 mL
Ratio Range tsp:	1.5 to 15 tsp
Water Flow Range:	0.05 to 14 GPM
Operating Pressure Range:	4.3 to 85 PSI
Available Housing Materials:	Polypropylene
Dimensions:	19 1/18" x 6 5/16"
Weight:	6 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104° F
Included Accessories:	6 ft clear suction tube, strainer, bypass, weight, mounting bracket and operating manual
Recommended Accessories:	200 mesh filter, check valve, pressure regulator, flow restrictor



NDS
NUTRIENT DELIVERY SYSTEM

The Nutrient Delivery System is customizable. More dosers can be added as needed.

NOTE: Installation illustrations are to be used as a reference guide only.

Dosatron International
2090 Sunnydale Blvd. • Clearwater, FL, USA
800-523-8499 • www.dosatronusa.com

Dosatron International, Inc. is an industry leader in water-powered, proportional chemical injectors. Dosatron products are manufactured according to ISO 9001:2000 and ISO 14001:2004 standards.